



ALWAYS KEEP

IMPORTANT RULES AND MAINTENANCE:

- Before every use check that all the screws are correctly tightened with the right torque as described in this manual.
- Keep always the threaded holes and every connection between carbon and aluminum (mast and wings to fuselage) clean and greased with Lithium grease code [MHW033] to avoid and prevent oxidation and corrosion due to salt water.
- After every use disassemble and wash all the parts with fresh water and dry them using a soft cloth.
- Do not expose to extreme temperatures or direct sunlight. Do not expose to temperatures above 100° C / 212° F.
- Store the foil in a safe and dry place in order to prevent injury and damage.
- During assembly make sure that the sand does not get into the threads.
- Never remove valves from boards.

DANGER!!!

THIS DISCLAIMER IS INTENDED TO MAKE THE USER OF THIS PRODUCT AWARE THAT ANY HYDROFOILING ACTIVITY CAN CAUSE INJURY OR DEATH TO HIMSELF OR TO THE PEOPLE AROUND HIM.

OBSERVE THE FOLLOWING SAFETY STANDARDS WHENEVER USING THIS PRODUCT:

- MAST, WINGS AND STABILIZER HAVE SHARP EDGES THAT MAY CAUSE SERIOUS INJURY OR DEATH.
- ALWAYS KEEP THE FOIL LEEWARD AND FAR AWAY FROM THE HUMAN BODY.
- PAY CLOSE ATTENTION TO YOUR LEGS AND FEET WHILE SWIMMING.
- THE BOARD WITH THE HYDROFOIL CAN BE VERY DANGEROUS FOR THE USER AND FOR THOSE AROUND HIM, ESPECIALLY IF THE USER LOSES CONTROL.
- NEVER USE THIS PRODUCT UNLESS YOU ARE IN GOOD PHYSICAL HEALTH.
- NEVER USE THIS PRODUCT UNLESS YOU ARE AN EXPERIENCED SWIMMER.
- ALWAYS USE ADEQUATE PROTECTION SUCH AS HELMET AND A FLOATING VEST.
- BE AWARE OF THE REGULATIONS IN FORCE IN YOUR AREA REGARDING SURFING, WINDSURFING AND KITESURFING.
- ALWAYS WEAR A SUITABLE HELMET.
- USE THE HYDROFOIL IN SAFE WATER CONDITIONS AND WITHIN YOUR ABILITIES, MAKE SURE YOU TAKE LESSONS BEFORE USING THIS PRODUCT IN THE WATER.
- AVOID SHALLOW WATERS WITH PRESENCE OF SWIMMERS, ROCKS OR OTHER SOLID OBSTACLES.
- DO NOT USE ANY KIND OF LEASH.
- DO NOT USE THIS PRODUCT UNDER THE INFLUENCE OF ALCOHOL, DRUGS OR MEDICATIONS.
- MINIMUM AGE OF RIDER IS 18 YEARS UNLESS UNDER CLOSE SUPERVISION OF A PARENT OR A LEGAL GUARDIAN.
- THIS PRODUCT IS DESIGNED FOR USE IN WATER ONLY.
- DO NOT USE THIS PRODUCT DURING THUNDERSTORMS AND/OR LIGHTNING CONDITIONS.
- THE USERS ARE RESPONSIBLE FOR THEIR SAFETY AND THE SAFETY OF THOSE AROUND THEM.
- BEFORE RIDING ENSURE THAT THE BOLTS ARE TIGHTENED WITH THE RIGHT TORQUE AS DESCRIBED IN THIS MANUAL.
- SAB GROUP S.R.L. IS NOT RESPONSIBLE FOR INJURIES, DEATH OR DAMAGE TO THE PRODUCT DUE TO MISUSE OR ANY USE NOT CONSISTENT WITH THESE INSTRUCTIONS.



ASSUMPTION OF RISK

SAB GROUP S.R.L. SHALL NOT BE LIABLE FOR SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES, LOSS OF PROFITS OR PRODUCTION OR COMMERCIAL LOSS IN ANY WAY CONNECTED WITH THE PRODUCT, WHETHER SUCH CLAIM IS BASED IN CONTRACT, WARRANTY, NEGLIGENCE, OR STRICT LIABILITY.

Further, in no event shall the liability of SAB GROUP S.R.L. exceed the individual price of the Product on which liability is asserted. As SAB GROUP S.R.L. has no control over use, setup, final assembly, modification or misuse, no liability shall be assumed nor accepted for any resulting damage or injury. By the act of use, setup or assembly the user accepts all resulting liability. If you as the Purchaser or user are not prepared to accept the liability associated with the use of this Product, you are advised to return this Product immediately in new and unused condition to the place of purchase.

LIMITED WARRANTY

SAB GROUP S.R.L. reserves the right to change or modify this warranty without notice and disclaims all other warranties, express or implied.

(a) This warranty is limited to the original Purchaser ("Purchaser") and is not transferable. REPLACEMENT AS PROVIDED UNDER THIS WARRANTY IS THE EXCLUSIVE REMEDY OF THE PURCHASER This warranty covers only those Products purchased from an authorized SAB GROUP S.R.L. dealer. Third party transactions are not covered by this warranty. Proof of purchase is required for warranty claims.


(b) Limitations- SAB GROUP S.R.L. MAKES NO WARRANTY OR REPRESENTATION, EXPRESS OR IMPLIED, ABOUT NONINFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OF THE PRODUCT. THE PURCHASER ACKNOWLEDGES THAT THEY ALONE HAVE DETERMINED THAT THE PRODUCT WILL SUITABLY MEET THE REQUIREMENTS OF THE PURCHASER'S INTENDED USE.

(c) Purchaser Remedy- SAB GROUP S.R.L.'s sole obligation hereunder shall be that SAB GROUP S.R.L. will, at its option, replace any Product determined by SAB GROUP S.R.L. to be defective In the event of a defect, this is the Purchaser's exclusive remedy. Replacement decisions are at the sole discretion of SAB GROUP S.R.L.. This warranty does not cover cosmetic damage or damage due to acts of God, accident, misuse, abuse, negligence, commercial use, or modification of or to any part of the Product. This warranty does not cover improper installation, operation, maintenance or attempted repair by anyone.

FOOTSTRAP ASSEMBLY

REQUIRED HARDWARE [MHW125]

- Self-tapping screws M5x25mm
- Washers $\varnothing 5,3 \times \varnothing 20 \times 1,6\text{mm}$



AUTOMATIC VALVE

THE VALVE IS TESTED AND CERTIFIED,
DO NOT REMOVE OR UNSCREW


ONLY WHEN STRICTLY NECESSARY REMOVE WITH A 16 MM SOCKET WRENCH AND THEN MAKE SURE TO RE-SCREW TIGHTLY (5Nm) TO PREVENT WATER INFILTRATION

MAST ASSEMBLY

Right tightening

- ① Insert the four special t-nuts (1) inside the board rails.
- ② Place the CPOK (2) on the board in the correct position
- ③ Insert the four screws M8x30 [MH155] and proceed to screw.*

* if you have the P02K, conical washers must be inserted before the M8x30 screws.



Check the latest version of this manual

